

E55 & T5 Topsides Programming Codes

CODE	ON	OFF (Default Options)
1	Jets-2 button operates 1 Speed Pump-2	Jets-2 button operates Pump-1 Low Speed
2	Jets-2 button operates Air Blower	Jets-2 button operates Pump-1 Low Speed
3	Jets-2 button operates 2 speed Pump-2 a- Pressing the Jets-2 button once will turn ON Pump-2 Low Speed b- Pressing again will turn OFF Pump-2 Low Speed & Turn ON Pump-2 High Speed c- Pressing again will turn Pump-2 OFF	Jets-2 button operates Pump-1 Low Speed
4	Jets-2 button operates Air Blower & 1 Speed Pump-2 a- Pressing the Jets-2 button once will turn ON Air Blower b- Pressing again will turn OFF Air Blower & Turn ON Pump-2 c- Pressing again will turn ON Air Blower & Pump-2 d- Pressing again will all OFF	Jets-2 button operates Pump-1 Low Speed
5	1 Filtration cycle	2 filtration cycle
6	Jets-1 button operates 2 Speed Pump-1 a- Pressing the Jets-1 button once will turn ON Pump-1 Low Speed b- Pressing again will turn OFF Pump-1 Low Speed & turn ON Pump-1 High Speed c- Pressing again will turn Pump-1 OFF	Jets-1 button operates Pump-1 High Speed a- Pressing the Jets-1 button once will turn ON Pump-1 High Speed b- Pressing again will turn OFF Pump-1 High Speed
7	Turning off the Thermostat Control Thermostat control Heater only and Pump-1 Low Speed is controled by the timer	Turning on the Thermostat Control Thermostat control Pump-1 Low Speed & Heater
8	This code must be OFF	This code must be OFF
9	Temperature in Celsius	Temperature in Fahrenheit
A	Turning on the Blower Timer System	Turning off the Blower Timer System
B	Spa Light, 3 Function for Fiber Optic a- Pressing the Light button once will turn ON Fiber Opric Light b- Pressing again will turn ON Fiber Optic Light & Color Wheel c- Pressing again will turn Both OFF	Spa Light, 2 function for Standard Light a- Pressing the Light button once will turn ON Spa Light b- Pressing again will Spa Light OFF
C	Heater shuts off when Pump-1 high speed relay comes On	Heater will operate with Pump-1 Low & High speed, Pump-2 or Blower
D	Heater shuts off when Pump-2 relay comes On	Heater will operate with Pump-1 Low & High speed, Pump-2 or Blower
E	Heater shuts off when Blower relay comes On	Heater will operate with Pump-1 Low & High speed, Pump-2 or Blower
F	Used for Circulating Pump that runs continuously	Thermostat control Pump-1 Low Speed & Heater
G	This code must be OFF	This code must be OFF

To enter the Programming Mode on the Topside Control:

- Press & hold the Light button for 6 seconds (until you see the filtration time setting).
- Press & hold for an additional second to see the filtration startup time.
- Press & hold the Light button again for an additional 11 seconds to enter the programming mode, the screen should now show the option for the first code (1-oF or 1-on)

To Program the Topside Control:

Once in the programming mode (you should see the option for the first code: 1-oF or 1-on), pressing the Temp button will cycle the option for that code between ON (on) and OFF (oF). Pressing the Light button will take you to the next code.

Simply continue in this fashion of setting the desired option (ON or OFF) of the code with the Temp button and pressing the Light button to progress to the next code, until you see the temperature readout again.